



## **Declaration of conformity**

For the following equipment:

Product Name: LED Driver

Model Designation: XLG-25-y, XLG-25I-y, XLG-50-y, XLG-50I-y (y=A, AB)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

RoHS Directive (2011/65/EU), (EU)2015/863

Energy-Related Products Directive (2009/125/EC)
Implementing measure COMMISSION REGULATION(EC) No 1194/2012

Low Voltage Directive (2014/35/EU):

EN 61347-1:2015 EN61347-2-13:2014/A1:2017 ENEC certificate No: 35-109039

## Electromagnetic Compatibility Directive (2014/30/EU):

## **EMI (Electro-Magnetic Interference)**

Conducted emission / Radiated emission

EN55015:2013+A1:2015

| Voltage flicker                       | EN61000-3-3:2013 |  |  |  |
|---------------------------------------|------------------|--|--|--|
| EMS (Electro-Magnetic Susceptibility) |                  |  |  |  |

| EN61547:2009             |                                  |         |                        |
|--------------------------|----------------------------------|---------|------------------------|
| ESD air                  | EN61000-4-2:2009                 | Level 3 | 8KV                    |
| ESD contact              | EN61000-4-2:2009                 | Level 2 | 4KV                    |
| RF field susceptibility  | EN61000-4-3:2006+A1:2008+A2:2010 | Level 3 | 10V/m                  |
| EFT bursts               | EN61000-4-4:2012                 | Level 3 | 2KV/5KHz/Power Line    |
| EFT bursts               | EN61000-4-4:2012                 | Level 3 | 1KV/5KHz/Control Line  |
| Surge susceptibility     | EN61000-4-5:2014                 | Level X | 4KV/Line-Line          |
| Surge susceptibility     | EN61000-4-5:2014                 | Level X | 6KV/Line-Earth         |
| Surge susceptibility     | EN61000-4-5:2014                 | Level 2 | 1KV/Control Line-Earth |
| Conducted susceptibility | EN61000-4-6:2014                 | Level 3 | 10V                    |
| Magnetic field immunity  | EN61000-4-8:2010                 | Level 4 | 30A/m                  |
|                          |                                  |         |                        |

Voltage dip, interruption EN61000-4-11:2004 30% dip 10 periods 100% interruptions 0.5 periods Note:

the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. Tests above are only to be performed with LEDs.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

To fulfill requirements of the latest FrP regulation for lighting fixtures, this LED power supply can only be use

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains(except XLG-25-y(y=A or AB) and XLG-50-y(y=A,AB)).

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation,

This Declaration is effective from serial number HB9xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Johnny Huang/Manager, Certification center:

(Name / Position)

(Signature)

Alex Tsai/Director, Marketing Department:

(Name / Position)

Taiwan

Jun. 20th, 2019

(Place)

(Date)

(Signature)